

Technical Data Sheet

HOOK-ON SYSTEM FITTING INSTRUCTIONS

We are one of the few PVC curtain suppliers that will come out and install your new curtains for you. If you would like a quote for us to fit your PVC curtains then please call us. **Tel: 01625 573 971**



- If required cut the stainless steel top track to the desired length, allow at least 25mm cover to each side if face fitting. Generally the track will come pre-cut to the required width.
- Mark the horizontal location for the track then use the 8 included screws to secure the stainless steel track to either the soffit or face of the opening. We also include rawl-plugs, but care must be taken to ensure these are suitable for your installation area.
- *N.B. Apart from pre-boxed Strip Curtain Kits which are the advertised length, we generally supply the PVC strips approximately 40-50mm over length to allow you to trim on-site once the curtain has been hung.*
- To achieve minimum overlap, hang the first strip onto the top track leaving three hook spaces before hanging the second strip, centralise and hang the third strip over the three hooks and repeat the procedure.
- To achieve maximum overlap, hang the first strip onto the top track leaving one hook space before hanging the second strip, centralise and hang the third strip over the one hook and repeat the procedure.
- Finally trim the bottom of each strip to the desired length using a sharp knife.

Animated installation videos can be viewed here: <https://www.pvc-curtains.com/hookon1.swf>

N.B. The animations may not run correctly when using Google Chrome.

PVC



Certificate Number: 14352
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971
FAX: +44 (0)1625 573250
Munsch & Co/PTM Ltd
Units AG2/3 Clarence Mill
Clarence Road, Bollington
Macclesfield, Cheshire
SK10 5JZ
United Kingdom